

Product type: REGUTEC

Product name: Pavement Curb

Product code:

OB2-XX-0300-000-00 **black**

OB2-XX-030E-010-00 **red**

OB2-XX-030E-020-00 **green**

OB2-XX-030E-040-00 **anthracite grey**

OB2-XX-030E-050-00 **dark brown**

(XX position is for product thickness)



PRODUCT MAIN DIMENSIONS

Thickness: 30, 40, 50 and 60 mm

Length and width: 1 000 × 250 mm

Basic characteristics

Material composition	recycled black SBR granulate 1,0 - 3,0 mm PU binder
Color	see product code
Color stability	the color may change when exposed to UV rays
Chemical resistance	do not use in the presence of oils, petroleum and its derivatives, strong acids and strong alkali
Edges type	beveled edges
Connection type	pressed/drilled holes for plastic pins
Thickness tolerance*	± 2,0 mm
Dimensional tolerance*	± 1,5 %
Weight tolerance	± 0,2 kg
Recycled content	> 90 %

Shipping and storage details

Length and width*	mm	1 000 × 250			
Thickness*	mm	30	40	50	60
Weight per piece	kg/pc	6,1	8,1	10,1	12,1
Pieces per pallet	pcs/pal	200	150	100	100
Pallet dimensions	mm	1 000 × 1 000			

**) The specified limit values are guaranteed only for the temperature range +23.0 +/- 5 °C, relative humidity 50.0 +/- 5 % according to EN 822, EN 823 and only if they are measured 24 hours after unpacking and relaxing of the products as described in Product installation requirements.*

Product installation requirements

Before the actual installation, at first, it is necessary to unpack the products from the pallet, spread them out on the surface on which they are going to be installed. Then let them lay on the surface to obtain the same temperature and let them relax their dimensions at least for 24 hours.

Use

Flexible and safe pavement curb

Guarantee

According to the current General Terms and Conditions of Regutec a.s.

Approved by REGUTEC a.s.

(electronic signature)



This technical specification is issued in accordance with current knowledge and experiences of the manufacturer as well as external and internal testing. The manufacturer reserves the right to change these data. The products may only be used for the purpose for which they were manufactured and tested. Otherwise, the manufacturer does not guarantee the lifetime or properties of the products or any damage that may occur. Products must not be exposed to strong acids, bases, oxidizing agents or oils. For cleaning, water or a mild detergent solution can be used without use of abrasive agents or tools. At the end of their product life, they can be 100 % recycled or landfilled under No. 191 204 Plastics and Rubber according to the Waste Catalogue with accordance to applicable local and national regulations.